



TECHNICAL DATA SHEET



Hardeners

Description:

EGC Hardeners are high quality-based hardeners for 2K products. They are especially designed for EGC 2K epoxy and polyurethane paint to optimized paint curing in a reasonable pot life.

Product preparation - Application



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.



Old or original paintwork well sanded and cleaned. Primer - Surfacer or Surfacer, sanded and cleaned. Surfaces must be prepared and cleaned correctly before application on Repair areas should be sanded with P500 - P600 (by machine) or P800 - P1000 (by hand) then cleaned using EGC cleaning thinner 111 or 111 J

Products	Purposes
H157	Hardener for 2K Epoxy Primer
H100	Hardener for 2K PUR Primer and Filler
H1802	Hardener for 2K PUR Topcoat (All Colors)
H1802 N	Hardener for 2K PUR Clearcoat 1800,1900
H1803	Hardener for 2K PUR Topcoat (Fast Hardener) (All Colors)
H020	Hardener for 2K PUR Cleracoat 063,1000
H8262	Hardener for HS 2K PUR Products

Shelf life: 6 months in good storing conditions (25°C, 65% humidity).

Remarks

- Ensure there is maximum ventilation during application.
- Wear the safety glasses and gloves.
- Keep out of reach of children.

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our product range.

The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.