



TECHNICAL DATA SHEET

Air Dry Clear Varnish



Description

One component Nitrocellulose based Clear Varnish, dries rapidly in the ambient temperature. It is used for refinish and touch up process, easy to apply and polish. Resistant to dust and humid weather.

Product preparation - Application



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.



EGC Basecoat: Surfaces must be dried / flashed-off in accordance with TDS before application.
Existing finishes: Surfaces must be sanded and degreased before application using EGC Cleaning Thinner no.111.



16:22 sec / (cup ford 4) using EGC Global Thinner or any suitable Thinner.



	Spray nozzle	Spray pressure
Conventional	1:3 - 1.5 mm	3.5 – 4.5 bar



Touch Dry 15-20 min.

Shelf life: 2 years in good storing conditions (25°C, 65% humidity).

Remarks

- Ensure there is maximum ventilation during application.
- wear the safety glasses and gloves.
- Keep out of reach of children.

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our product range.

The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.