



TECHNICAL DATA SHEET



MS Base Coat (Metallic & Solid colors)

Description

It is a concentrated mixture of pre-ground high quality solid or metallic pigments in a fast-drying mat paint, ready to be covered wet on wet with a brilliant glossy protective clear varnish.

Product preparation - Application



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.



Old or original paintwork well sanded and cleaned. Primer-Surfacer or Surfacer, sanded and cleaned. Surfaces must be prepared and cleaned correctly before application. Repair areas should be sanded with P500-P600 (by machine) or P800-P1000 (by hand) and cleaned with EGC cleaning thinner 111.



12:16 sec / (cup ford 4) using EGC global thinner or fast thinner 1807W for winter or the slow thinner 1812S for summer.



	Spray nozzle	Spray pressure
Conventional	1.2 - 1.4	3 - 4 bar



Apply the clear coat wet on wet after 15 – 20 min. at ambient temperature.



Shelf life: 2 years in good storing conditions (25°C, 65% humidity).

Remarks

- Ensure there is maximum ventilation during application.
- Wear the safety glasses and gloves.
- Keep out of reach of children.

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our product range.

The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.