



TECHNICAL DATA SHEET

NC PUTTY



Description:

A special glazing body filler based on modified alkyd resins, Nitrocellulose and selected extenders. It is formulated to give an extra thickness to the surface and as a leveling filler to all wood & steel surfaces, with a good sanding properties. It gives a homogenous surface after finishing.

Features

- Provides good flexibility.
- Has a fine homogeneous structure.
- Provides good adhesion to bare steel and a variety of other substrates.
- Allows easy sanding, leaving a smooth finish without air bubbles.
- Provides easy, fast filling with no sagging.

Product preparation - Application



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.



Clean with degreasing Thinner 111 or 111J. Sand with P180 dry, Do not use the thermoplastic substrates.



Apply smooth film immediately after mixing, avoiding air entrapment.



23 °C 15 - 20 min.



Dry sand P80 - P180
Final sand P180 - P240

Shelf life: 1 year in good storing conditions ($23 \pm 2^{\circ}\text{C}$ $50 \pm 5\%$ humidity). Keep away from direct sunlight.

Remarks

- Do not add more hardener than recommended to avoid bleeding and spot marking.
- Reaction temperature should be at least $+5^{\circ}\text{C}$.

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our product range.

The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.