



# TECHNICAL DATA SHEET

## AUTO PRO - 707 Undercoat



### Description:

A high build thixotropic sprayable air dry coating for car underbody. It provides excellent anticorrosive and stone chip protection. Easy Application using a spray gun attached directly to the can

### Product preparation - Application



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.



EGC undercoat 707 should be applied over rust free and degreased bare metal. For longer resistance to corrosion, it is recommended to apply an anticorrosive primer prior to overcoating with undercoat 707.



Add 10-15% air dry Thinner (if needed).



Apply 1-2 coats of undercoat 707.  
Nozzle: 6-8 mm; Pressure: 3-5 bar



Dry to Touch	Dry to Handle
15-30 min	2-3 hr.

**Shelf life:** 1 year in good storing conditions ( $23 \pm 2^\circ\text{C}$   $50 \pm 5\%$  humidity). Keep away from direct sunlight.

### Remarks

- Ensure there is maximum ventilation during application.
- Wear the safety glasses and gloves.
- Keep out of reach of children.

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our product range.

The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.