



TECHNICAL DATA SHEET



Wash Primer - 208

Description:

Wash Primer 208 is a chromate free wash Primer which ensure a high degree of corrosion protection on bare metal. It's characterized by an excellent adhesion on steel, aluminum and galvanized steel.

Features:

- Chromate free.
- Corrosion protection.
- Excellent adhesion.
- Excellent topcoat holds out.


Product preparation - Application



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.



Bare steel sanded and cleaned.
Galvanized steel or aluminum, sanded and cleaned.
Old or original paintwork well sanded and cleaned.
Using the degreasing Thinner no.111.



Dilute with EGC Thinner no.127 or Global Thinner to give 14-16 /sec (cup ford 4).



Type of spray gun	Conventional Gravity
Fluid tip (mm)	1.1 - 1.4
Spraying pressure at the gun (bars)	3 - 5 bars



Dry at ~ 23 °C for 15 - 20 min.

Shelf life: 6 months in good storing conditions 23 ± 2°C 50 ± 5 % humidityC). Keep away from direct sunlight.

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our product range.

The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.